

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1. (Currently Amended) An air circulation device comprising:

a self standing housing assembly having a front face portion, a main base portion, and a rear face portion, the base portion having a thin low profile 12 volt direct current motor and a fan blade;

an electrical connection device coupled with said motor, said electrical connection device for coupling with a socket in a motor vehicle;

a rigid casing sealing the motor and associated motor bearings, said rigid casing providing protection against damage from external forces, said rigid casing creating a liquid impermeable seal enabling said air circulation device to be subjected to highly pressurized liquids for cleaning said fan blades while preventing corrosion and damage due to the liquid and said casing covering said motor having a thickness around one inch to provide a low profile motor assembly.

2. (Cancelled)

3. (Cancelled)

4. (Cancelled)

5. (Original) The air circulation device of Claim 1, wherein the casing is made of a rigid, non-corrosive material such that it is able to withstand external forces and pressures such as those exerted by the application of highly pressurized liquids.

6. (Cancelled)

7. (Original) The air circulation device of Claim 1, wherein the base portion contains at least one elongated support portion.

8. (Original) The air circulation device of Claim 7, wherein the elongated support portion is capable of being pivotally disposed in an extended position, a contracted position, or any desired intermediary position.

9. (Original) The air circulation device of Claim 8, wherein the elongated support portion is secured into the extended position through the cooperation of a knob, disposed upon the elongated support portion, and a dimple, formed in the bottom face of the main base.

10. (Previously Presented) An air circulation device comprising:

a housing assembly having a front face portion, a main base portion, and a rear face portion, the base portion having a motor and a fan blade;

wherein a bottom face of the main base portion includes at least one elongated support member secured to said bottom face by a fastening member; and

wherein the elongated support portion is pivotally disposed about said fastening member and manually positioned in an extended position, a contracted position, or any desired intermediary position between the extended and contracted position for supporting the air circulation device in a number of different elongated support member positions; and

said elongated support portion is secured into the extended position through the cooperation of a knob, disposed upon the elongated support portion, and a dimple, formed in the bottom face of the main base.

11. (Original) The air circulation device of Claim 10, wherein the motor is powered by 12-volt direct current.

12. (Cancelled)

13. (Previously Presented) The air circulation device of Claim 10, wherein the motor as well as motor bearings associated with said motor are sealed within a rigid casing.

14. (Original) The air circulation device of Claim 13, wherein the casing is sealed so as to be impermeable to liquid.

15. (Original) The air circulation device of Claim 13, wherein the casing is made of a rigid, non-corrosive material such that it is able to withstand external forces and pressures such as those exerted by the application of highly pressurized liquids.

16. (Original) The air circulation device of Claim 10, wherein the device, excluding the motor and associated casing, is made of a polymeric material.

17. (Cancelled)

18. (Cancelled)

19. (Original) The air circulation device of Claim 10, wherein the housing has a thickness of about three inches.